

## PRODUCT SPECIFICATION



The mark of  
responsible forestry  
FSC® C117321

# SAVA PRINT CREAM

Toned, surface treated, machine finished offset paper  
with higher smoothness.

PROPERTY	UNIT	VALUE	
Grammage	ISO 536	g/m <sup>2</sup>	55      60      70      80      ±2.5%
Specific volume	ISO 534	cm <sup>3</sup> /g	1.25–1.35
Breaking strength	ISO 1924	N	38      43      48      53      *
Opacity	ISO 2471	%	90      92      94      *
Colour	ISO 5631-2		
L			92.5      *
a			2.5      *
b			14.5      *
Roughness Bendtsen	ISO 8791-2	ml/min	100      *

\* Typical values

### OTHER CHARACTERISTICS

#### Reel dimensions:

- a) width (cm): 25–210
- b) diameter (mm): 1000–1250(1450)
- c) core diameter (mm): 70, 76, 100, 120, 150

#### Reel marking:

On the header and the running surface: producer's name, paper grade, order, reel No, grammage (g/m<sup>2</sup>), reel width & diameter (cm), paper length (m), reel position, gross weight (kg), PO, date of production, clamping force (kN), number of glued joints, unwinding direction, barcode, notes at customer's request; possible marking adjustments (paper grade, producer) at customer's request.

Glued joints – marked on the reel: max. 1 per reel.

#### Sheet dimensions:

A1 (B1) – A0 deviations according to the ISO 216 Standard; sheeting grammages ≥50 g/m<sup>2</sup>

#### Pallet marking:

On both sides: producer's name, paper grade, order, pallet No, sheet size (mm), grain direction, grammage (g/m<sup>2</sup>), number of sheets, PO, gross & net weight (kg), date of production, barcode, possible marking adjustments (paper grade, producer) at customer's request.

### APPLICATION

For periodicals, books, magazines, catalogues and other promotional publications, picture books and office paper; for multi-colour and black&white heat-set offset printing, for digital printing and sheet-fed printing.

### PACKING

Reels wrapped in multiple layers of waterproof paper laminate. Pallets with lids wrapped in transparent PE foil fastened by PET straps; additional wrapping in multiple layers of waterproof paper laminate possible at customer's request.

### NOTES

**Ecological grade: ECF;** made from recycled fibres obtained from recovered paper in deinking process.

Paper is classified in class **LDK 6-40** (according to DIN 6738).

**FSC®:** FSC Mix Credit certified product can be provided upon request.

Sheeting of lower grammages possible (prior agreement required).

Head of QM  
Aleksandra Račič Kozmus

Technical Director  
Milena Resnik

Krško, 15 October 2021